

## Declaration of performance

<ol> <li>Unique Identification of the product</li> </ol>	luct:	ifica	Ident	aue	Uni	1
--	-------	-------	-------	-----	-----	---

- 2 Type, batch, or serial number for identification:
- 3 Intended Use:
- 4 Name & Address of the manufacturer:

Fibolite 7.3 N/mm<sup>2</sup>

Fibolite 7.3

In walls, columns and partitions - Load and non-load bearing

Plasmor Ltd PO Box 44, Womersley Road Knottingley West Yorkshire WF11 0DL

t: 01977 673221 e: technical@plasmor.co.uk

- 5 System of Assessment / Attestation of conformity:
- 6 Notified Factory production control for inspection, factory production control and continual surveillance:

Not Applicable

4

7 Declaration of Performance

Г

Essential Characteristic	Performance	Harmonised Standard		
Dimensions	Length (mm)	440		
	Height (mm)	215		
	Width (mm)	75 - 215		
Compressive Strength Category	Category 2	_		
Compressive Strength (mean)	7.3N/mm <sup>2</sup>			
Dimensional Stability (Shrinkage)	=< 0.60mm/m			
	Shear (Tabulated BS EN 998)	0.15N/mm <sup>2</sup>	BS EN 771-3	
Bond Strength	Flexural	N.P.D.	(2011)	
Reaction to Fire	Euro Class A1			
Water Absorption	N.P.D.			
Water Vapour diffusion coefficient, $\boldsymbol{\mu}$	Tabulated EN 1745 - Table A 6	5 / 15		
Gross Dry Density	950 KG/m <sup>3</sup>	]		
Configuration	Group 1 Solid	]		
Dimensional Tolerances	nensional Tolerances			
Thermal Conductivity W/(m.K)	Assessed on Thermal tests and graphed, EN 1745 - Table A 6	0.243		
	$\lambda$ 10,dry,mat P = 50%			
Durability against Freeze Thaw	Not to be left exposed			

8 The performance of the products identified in points 1 & 2 is the conformity of the declared performance in point 7. This declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of Plasmor Ltd

J A Slater **Managing Director** 

Managing Director Plasmor Group of Companies 2023

6209/1122