

## Declaration of performance

(No. 024\_02)

1 Unique Identification of the product:

2 Type, batch, or serial number for identification:

3 Intended Use:

4 Name & Address of the manufacturer:

**Stranlite Foundation Blocks** 

**Stranlite Foundation Blocks** 

Civil Engineering, Load and non-load bearing

Plasmor Ltd

PO Box 44, Womersley Road

Knottingley West Yorkshire WF11 0DL

t: 01977 673221

e: technical@plasmor.co.uk

5 System of Assessment / Attestation of conformity:

Notified Factory production control for inspection, factory production control and continual surveillance: 4

Not Applicable

7 Declaration of Performance

Essential Characteristic		Performance	Harmonised Standard
Dimensions	Length (mm)	Standard 250/275* Weight Saver 215	
	Height (mm)	Standard 140 Weight Saver 140	
	Width (mm)	Standard 300 Weight Saver 390	
Compressive Strength Category		Category 2	
Compressive Strength (mean)		7.3N/mm²	
. ,		10.4N/mm <sup>2</sup>	
Dimensional Stability (Shrinkage)		=< 0.60mm/m	
Bond Strength	Shear (Tabulated BS EN 998)	0.15N/mm <sup>2</sup>	BS EN 771-3 (2011)
	Flexural	N.P.D.	
Reaction to Fire		Euro Class A1	
Water Absorption		N.P.D.	
Water Vapour diffusion coefficient, μ	Tabulated EN 1745 - Table A 8	5 / 15	
Gross Dry Density		1400 KG/m <sup>3</sup>	
Configuration		Group 1 Solid	
Dimensional Tolerances		Category D1	
Thermal Conductivity W/(m.K)	Tabulated EN 1745 - Table A 8	0.37	
	$\lambda$ 10,dry,mat P = 50%		
Durability against Freeze Thaw		Not to be left exposed	1

The performance of the products identified in points 1 & 2 is the conformity of the declared performance in point 7. This declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of Plasmor Ltd

J A Slater

Managing Director
Plasmor Group of Companies