

Declaration of performance

(No. 001_02)

1 Unique Identification of the product:

2 Type, batch, or serial number for identification:

3 Intended Use:

4 Name & Address of the manufacturer:

Stranlite Standard & Paint-grade

Stanlite

In walls, columns and partitions - Load and non-load bearing

Plasmor Ltd PO Box 44, Womersley Road Knottingley West Yorkshire WF11 0DL

t: 01977 673221

e: technical@plasmor.co.uk

5 System of Assessment / Attestation of conformity:

6 Notified Factory production control for inspection, factory production control and continual surveillance: 4

Not Applicable

7 Declaration of Performance

Essential Characteristic		Performance	Harmonised Standard
Dimensions	Length (mm)	Standard 440 Modular 390	
	Height (mm)	Standard 215 Modular 190	
	Width (mm)	75 - 215	
Compressive Strength Category		Category 2	
Compressive Strength (mean)		3.6N/mm ²	
		4.2N/mm ²	
		7.3N/mm ²	
		10.4N/mm ²	BS EN 771-3
Dimensional Stability (Shrinkage)		=< 0.60mm/m	(2011)
Bond Strength	Shear (Tabulated BS EN 998)	0.15N/mm ²	
	Flexural	N.P.D.	
Reaction to Fire		Euro Class A1	_
Water Absorption		N.P.D.	
Water Vapour diffusion coefficient, μ	Tabulated EN 1745 - Table A 8	5 / 15	
Gross Dry Density		1400 KG/m³	
Configuration		Group 1 Solid	
Dimensional Tolerances		Category D1	
Thermal Conductivity W/(m.K)	Tabulated EN 1745 - Table A 8	0.37	
	λ 10,dry,mat P = 50%		
Durability against Freeze Thaw		Not to be left exposed]

The performance of the products identified in points 1 & 2 is the conformity of the declared performance in point 7. This declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of Plasmor Ltd

J. A. Slate

J A Slater Managing Director Plasmor Group of Companies 2023