

## Declaration of performance

(No. 005\_02) Flooring

1 Unique Identification of the product:

2 Type, batch, or serial number for identification:

System of Assessment / Attestation of conformity:

Notified Factory production control for inspection, factory production control and continual surveillance:

3 Intended Use:

4 Name & Address of the manufacturer:

100mm Aglite Ultima Flooring Blocks

Aglite 4.2

Structural, Concrete Blocks for Beam & Block floor systems

Plasmor Ltd

PO Box 44, Womersley Road

Knottingley West Yorkshire WF11 0DL

t: 01977 673221

e: technical@plasmor.co.uk

2+

BSI Group, Davy Avenue, Knowhill, Milton Keynes, MK5 8PP (Reference 0086 - CPR - 601346)

7 Declaration of Performance

Essential Characteristic		Performance	Harmonised Standard
Dimensions	Length (L)	215mm	
	Height (H)	96mm	
	Width (W)	437mm	
Bond Strength	Minimum resistance to concentrated loads	3.5kN (R1)	BS EN 15037- 2:2009 + A1:2011 (Annex ZA)
	Longitudinal compressive strength	NPD < 20MPa	
Reaction to Fire	Spread of flame will not arise as the material is covered by a surface finish	Euro Class 1	
Sound Insulation	Gross Dry Density	1050KG/m <sup>3</sup>	
	Configuration	Group 1 Solid	
Detailing	Geometrical Properties	TF2	
	Production Tolerances	T2	
Thermal Conductivity W/(m.K)	Assessed on Thermal tests and graphed, EN 1745 - Table A 6	0.273	
	$\lambda$ 10,dry,mat P = 50%		
Durability against Freeze Thaw		Ambient Conditions	

The performance of the products identified in points 1 & 2 is the conformity of the declared performance in point 7. This declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of Plasmor Ltd

J A Slater Managing Director

Plasmor Group of Companies 2023