

## Declaration of performance

(No. 021\_02) Flooring

1 Unique Identification of the product:

2 Type, batch, or serial number for identification:

System of Assessment / Attestation of conformity:

Notified Factory production control for inspection, factory production control and continual surveillance:

3 Intended Use:

4 Name & Address of the manufacturer:

100mm Stranlite Flooring Blocks

Stranlite JB1

Structural, Concrete Blocks for Beam & Block floor systems

Plasmor Ltd PO Box 44, Womersley Road Knottingley West Yorkshire WF11 0DL

t: 01977 673221

e: technical@plasmor.co.uk

2+

BSI Group, Davy Avenue, Knowhill, Milton Keynes, MK5 8PP (Reference 0086 - CPR - 601346)

7 Declaration of Performance

Essential Characteristic		Performance	Harmonised Standard
Dimensions	Length (L)	215mm	
	Height (H)	96mm	
	Width (W)	437mm	
Bond Strength	Minimum resistance to concentrated loads	3.5kN (R1)	BS EN 15037- 2:2009 + A1:2011 (Annex ZA)
	Longitudinal compressive strength	NPD < 20MPa	
Reaction to Fire	Spread of flame will not arise as the material is covered by a surface finish	Euro Class 1	
Sound Insulation	Gross Dry Density	1400KG/m <sup>3</sup>	
	Configuration	Group 1 Solid	
Detailing	Geometrical Properties	TF2	
	Production Tolerances	T2	
Thermal Conductivity W/(m.K)	Assessed on Thermal tests and graphed, EN 1745 - Table A 8	0.37	
	$\lambda$ 10,dry,mat P = 50%		
Durability against Freeze Thaw		Ambient Conditions	7

The performance of the products identified in points 1 & 2 is the conformity of the declared performance in point 7. This declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of Plasmor Ltd

J. A. Slater

J A Slater Managing Director

6209/1122