

PLASMOR LIMITED - DECLARATION OF PERFORMANCE (No. 015_02)

- 1 Unique Identification of the product: **Plasmor Airey Block & Cut Corner**
- 2 Type, batch, or serial number for identification: **Airey Block**
- 3 Intended Use: **In walls, columns and partitions – Load and non-load bearing**
- 4 Name & Address of the manufacturer
Plasmor Ltd
PO Box 44, Womersley Road
Knottingley
West Yorkshire
WF11 0DL 01977 673221 technical@plasmor.co.uk
- 5 System of Assessment / Attestation of conformity **4**
- 6 Notified Factory production control for inspection, factory production control and continual surveillance:- **Not Applicable**
- 7 Declaration of Performance

Essential Characteristic		Performance	Harmonised Standard
Dimensions	Length (mm)	440 Standard 390 Cut Corner	BS EN 771-3 (2011)
	Height (mm)	215	
	Width (mm)	175	
	Compressive Strength Category	Category 2	
Compressive Strength (mean)		3.6N/mm ²	
Dimensional Stability (Shrinkage)		=< 0.60mm/m	
Bond Strength	Shear (Tabulated BS EN 998)	0.15N/mm ²	
	Flexural	N.P.D.	
Reaction to Fire		Euro Class A1	
Water Absorption		N.P.D.	
Water Vapour diffusion coefficient, μ	Tabulated EN 1745 - Table A 6	5 / 15	
Gross Dry Density		1000 KG/m ³	
Configuration, special shape see attached sketch		Group 1 Solid	
Dimensional Tolerances		Category D1	
Thermal Conductivity W/(m.K)	Tabulated EN 1745 - Table A 6	0.3	
	$\lambda_{10,dry,mat} P = 50\%$		
Durability against Freeze Thaw		Not to be left exposed	

- 8 The performance of the products identified in point 1 & 2 is the conformity of the declared performance in point 7. This declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of Plasmor Ltd



..... J.A.Slater (Managing Director)
 Knottingley, West Yorkshire, June 2014

