

TEXTURED ARCHITECTURAL MASONRY

The close textured face of the **TEXTURED** range offers an interesting and attractive external or internal wall surface. It is a practical and exciting alternative to smooth face blocks. Textured Masonry, available in eight pleasing colours, provides specifiers with the best practical masonry solution.

TEXTURED

ARCHITECTURAL MASONRY



COTSWOLD YELLOW



BARLEY



BUFF



RUSTIC RED



SLATE GREY



NATURAL WHITE



GREEN



HEATHER

METRIC SIZES AND TYPES

Work Size 440mm x width x 215mm
Co-ordinating Size 450mm x width x 225mm

Type	90mm	100mm	140mm	190mm	215mm
Solid					
Hollow/Cellular					
Multicore					

METRIC MODULAR SIZES AND TYPES

Work Size 390mm x width x 190mm
Co-ordinating Size 400mm x width x 200mm

Type	90mm	100mm	140mm	190mm	215mm
Solid					
Hollow/Cellular					
Multicore					

PROPERTIES AND PERFORMANCE

Mean Compressive Strength

	Solid	17.5 N/mm ²
	Hollow/Cellular	10.4 N/mm ²
	Multicore	10.4 N/mm ²

Dry Density

	2000 Kg/m ³
--	------------------------

Thermal Value (at 3% moisture)

	Solid k	=	1.127W/m°C
	Cellular k	=	0.540W/m°C

Moisture Movement

	Not greater than 0.30mm/m
--	---------------------------

Sound Insulation

	Average reduction 43 - 50dB
--	-----------------------------

Fire Resistance

	Textured is manufactured from Class 1 Fire Resistant Aggregate as defined in BS 5628 Part 3 and complies with BS EN 1996-1-2005.
--	--



TECHNICAL HELPLINE: 01977 673221