Plasmor
CONCRETE PRODUCTS

SUSTAINABILITY REPORT 2018
Expanded Clay Production

Sustainability Principle	Performance Indicator	Unit of Expression	PLASMOR PERFORMANCE 2018	2017	2016	2015	2014	2013	2012	Target 2020
Climate change and energy	Energy used in production as a proportion of production output	kWh/m^3	241.82	222.72	227.57	220.47	211.3	223.7	245.9	Reduce overall kWh/tonne of energy used in production by 10% against 2012 baseline
	CO_2 emissions as a proportion of production output	kg CO_2 per m^3	46.61	42.12	42	40.84	42.1	44.0	48.1	Reduce CO_2/tonne emissions from production by 20% against 2012 baseline
Resource Use	Material diverted from the waste stream for use as a fuel source as a proportion of production output	kg per tonne	52.7	52.5	50.1	50.3	46.2	45.8	44.0	Increase by 2.5% per year
Management Systems	Tonnage and production sites covered by certified ISO 9001	% production % sites	100 100	100 100	100 100	100 100	100 100	100 100	100 100	95%
	Tonnage and production sites covered by certified ISO 14001	% production % sites	100 100	100 100	100 100	100 100	100 100	100 100	100 100	95%
	Tonnage and production sites covered by BES 6001	% production % sites	100 100	100 100	100 100	100 100	100 100	100 100	100 100	95%
Employment and skills	% of employees covered covered by UKAS certified 9001/14001/18001 (Training and Competence)	%	100	100	100	100	94	94	94	100%
Complaints and prosecutions	Local Community Complaints Convictions for air and water emissions per year	Number per year Number per year	5 0	2 0	4 0	4 0	0 0	0 0	0 0	Zero Zero